

### Quick Release Couplings - Series-Q

**Applications**

- Designed for applications requiring a quick connection and/or disconnection of a pipe joint

**Comparable to**

- Victaulic's #78
- Grinnell's #7003

**Features**


- A locking pin through the handle prevents accidental opening of the coupling
- See page 962 for replacement gaskets

**Materials**

- Ductile iron body with zinc plating and steel safety clip



| Nominal Size | Pipe O.D. | Maximum Working Pressure<br>PSI at 70°F (21°C) | Maximum End Load<br>(Lbs.) | Ductile Iron               |                                      |
|--------------|-----------|--|----------------------------|----------------------------|--------------------------------------|
|              |           |  |                            | Part #<br>with EPDM gasket | Part #<br>with Nitrile Rubber gasket |
| 1-1/2"       | 1.900"    | 300  | 850                        | H315                       | H315BU                               |
| 2"           | 2.375"    | 300  | 1329                       | H32                        | H32BU                                |
| 2-1/2"       | 2.875"    | 300  | 2120                       | H325                       | H325BU                               |
| 3"           | 3.500"    | 300  | 2886                       | H33                        | H33BU                                |
| 4"           | 4.500"    | 300  | 4771                       | H34                        | H34BU                                |
| 6"           | 6.625"    | 300  | 10341                      | H36                        | H36BU                                |



Dimensions

| A       | B      | C      |
|---------|--------|--------|
| 4-3/4"  | 3-1/2" | 1"     |
| 5-1/2"  | 3-3/4" | 1-7/8" |
| 5-7/8"  | 4-3/4" | 1-7/8" |
| 7-1/4"  | 5-1/4" | 1-7/8" |
| 8-1/2"  | 6-1/2" | 2"     |
| 10-5/8" | 8-1/2" | 2"     |

