

**FSA-Storz x Rigid Female**

**Application**

- For use wherever a non-valved, locking coupling is required

**Specification**

- Working pressure: 150 PSI at 70°F (21°C)

**Materials**

- Nitrile rubber gaskets
- Cast aluminum lock lever assembly on 4", 5", and 6"

**Approval**

- Anodized components per MIL-A-8625 Type III Class 1

**Storz x NST (NH) Female**

| Storz Size | NST (NH) Female Thread | 6061-T6 Forged Aluminum Part # |
|------------|------------------------|--------------------------------|
| 1-1/2"     | 1-1/2"                 | FSA1515F                       |
| 2"         | 1-1/2"                 | FSA2015F                       |
|            | 2-1/2"                 | FSA2025F                       |
| 2-1/2"     | 2-1/2"                 | FSA2525F                       |
| 3"         | 2-1/2"                 | FSA3025F                       |
|            | 2-1/2"                 | FSA4025F                       |
|            | 3"                     | FSA4030F                       |
|            | 4"                     | FSA4040F                       |
| 4"         | 4-1/2"                 | FSA4045F                       |
|            | 5"                     | FSA4050F                       |
|            | 6"                     | FSA4060F                       |
|            | 2-1/2"                 | FSA5025F                       |
|            | 3"                     | FSA5030F                       |
| 5"         | 4"                     | FSA5040F                       |
|            | 4-1/2"                 | FSA5045F                       |
|            | 5"                     | FSA5050F                       |
|            | 6"                     | FSA5060F                       |
| 6"         | 6"                     | FSA6060F                       |



**Storz x NPT Female**

| Storz Size | NPT Female Thread | 6061-T6 Forged Aluminum Part # |
|------------|-------------------|--------------------------------|
| 1-1/2"     | 1"                | FSA1510T                       |
|            | 1-1/2"            | FSA1515T                       |
| 2"         | 1-1/2"            | FSA2015T                       |
|            | 2"                | FSA2020T                       |
| 2-1/2"     | 1-1/2"            | FSA2515T                       |
|            | 2"                | FSA2520T                       |
|            | 2-1/2"            | FSA2525T                       |
|            | 3"                | FSA2530T                       |
| 3"         | 3"                | FSA3030T                       |
|            | 3"                | FSA4030T                       |
| 4"         | 4"                | FSA4040T                       |
|            | 6"                | FSA4060T                       |
|            | 3"                | FSA5030T                       |
| 5"         | 4"                | FSA5040T                       |
|            | 5"                | FSA5050T                       |
|            | 6"                | FSA5060T                       |
|            | 4"                | FSA6040T                       |
| 6"         | 6"                | FSA6060T                       |



**Storz x NPSH Female**

| Storz Size | NPSH Female Thread | 6061-T6 Forged Aluminum Part # |
|------------|--------------------|--------------------------------|
| 1-1/2"     | 1-1/2"             | FSA1515S                       |
| 2"         | 1-1/2"             | FSA2015S                       |
| 2-1/2"     | 2-1/2"             | FSA2525S                       |
| 4"         | 4"                 | FSA4040S                       |



NOTE: All adapters are made to approved Dixon® specifications.

NOTE: Replacement washers can be found on page 827

N